

Operating & Monitoring



cloudPanel





Starting with the small cloudPanels up to the large, high-performance PanelPC, we offer you the complete HMI product range.

Often the interaction between humans and machines is carried out via operating devices which are connected with the heart of the installations. Right here the operating devices are deployed. Whether from the smallest installation up to large, multiple networked machines that are deployed worldwide.

Regardless of which system you choose they are all founded on the same basis and so they can be used for all project engineering and programming, starting from the smallest up to the largest one. Only the hardware changes. Our target is to have the right solution for each customer and each installation.

Our Touch Panels have proven themselves in many applications in all industries for years. The range of the systems deployed is as wide as the applications and technologies in the respective installation.

cloudPanels – Ideal for smaller applications, when your project doesn't require all the features of the smartPanels!

The cloudPanels are optimized for web applications and the perfect companion for WebVisu projects. Since WebVisu is already integrated in the Engineering Tool SPEED7 Studio, visualization via the new cloudPanel is easy as pie: It runs inside the PLC and is accessed by the cloudPanel via its optimized HTML5 browser. Rendering a cost effective visualization solution, that specially benefits smaller projects.

Your PLC has a Webserver? Perfect!

Then just let us show you the visualization via cloudPanels.

- optimized for web applications
- location independent use
- HTML5 browser for smooth web-applications experience





smartPanels – The smartest choice for high usability, performance and featuring OPC UA connectivity in one panel.

Quality

 Robust and durable – IP66 protection rating

Functionality

 The smartPanels come with Movicon 11 and Windows Embedded Compact 7, for resource hungry applications

smartPanels in detail

- Slim Profile
- Robust housing . IP66
- Powerful scripting capabilities

Open for teleservice

 By means of the VNC-Client software you can also have access to your smartPanel via teleservice The smartPanels are optimally designed for medium-sized applications. They stand for high usability and connectivity. Equipped with Movicon 11 Standard, the user is practically unrestricted in terms of tags, screens, recipes, alarms, etc.

| smart | TP 304-SM | TP 307-SM | TP 310-SM |
|---------------------|---|----------------------|-----------|
| Operating System | | ndows Embedded Compa | |
| Runtime | Movicon 11 | | |
| cloud | TP 104-CL | TP 107-CL | TP 110-CL |
| Operating System | | Linux | |
| Runtime | | Webvisu | |
| Display size [Zoll] | 4,3 | 7 | 10 |
| Resolution [Pixel] | 480x272 | 800x480 | 1024x600 |
| Touch screen | | resistive | |
| Processor | ARM Cortex-A8 1GHz | | |
| Interfaces | 1x RS232/422/485, 1x USB-A, 1x Ethernet | | |
| int. RFID Reader | | ÷ | |
| Work memory [MB] | 512 | | |
| Load memory [GB] | 4 | | |
| Cardslot | - | | |
| Housing | plastic | | |
| Protection | Front: IP 66 / Rear: IP 20 | | |

professional Panel



professional Panels – extremely powerful Touch Panels with unique features and high scalability. Offered with or without Movicon 11 runtime and optional RFID module.

With the professional Panels you are prepared for demanding the most dechoose from many combination options exactly the panel which best

fits to your application. It is not an issue if you have a different preferenmanding automation tasks. You can ce for visualization software/runtime. Our professional Panels can cope wonderfully with many Runtimes of

other manufacturers. We will gladly customize the devices if you want your company name featured in them.

| Resolution Pixel 320x240 640x480 800x600 800x600 1024x768 Touch screen | | TP 605CQ | TP 606C | ((●)) RFID TP 608C | ((•))RFID | ((•)) RFID |
|---|---------------------|---|--------------------------|-------------------------|---|--------------------|
| Touch screen | Display size [Zoll] | 5,7 | 6,5 | 8,4 | 10,4 | 12,1 |
| Name | Resolution [Pixel] | 320x240 | 640x480 | 800x600 | 800x600 | 1024x768 |
| Interfaces | Touch screen | | | resistive | | |
| 1x RS422/485 | Processor | XScale-CPU 800MHz | XScale-CPU 1066MHz | XScale-CPU 1066MHz | XScale-CPU 1066MHz | XScale-CPU 1066MHz |
| Work memory [MB] 128 256 256 256 256 User Memory [MB] 2048 512 512 512 512 Cardslot CF + SD/MMC Housing Die-cast aluminium Protection front: IP65 rear: IP20 Operating System Windows Embedded CE 6.0 Prof. | Interfaces | 1x RS422/4 1x USB-A 1x USB-B 1x Ethernet | | | 1x RS422/485 2x USB-A 1x USB-B 2x Ethernet | |
| User Memory [MB] 2048 512 512 512 512 Cardslot CF + SD/MMC Housing Die-cast aluminium Protection front: IP65 rear: IP20 Operating System Windows Embedded CE 6.0 Prof. | int. RFID Reader | - | - | • | • | • |
| Cardslot CF + SD/MMC Housing Die-cast aluminium Protection front: IP65 rear: IP20 Operating System Windows Embedded CE 6.0 Prof. | Work memory [MB] | 128 | 256 | 256 | 256 | 256 |
| Housing Die-cast aluminium Protection front: IP65 rear: IP20 Operating System Windows Embedded CE 6.0 Prof. | User Memory [MB] | 2048 | 512 | 512 | 512 | 512 |
| Protection front: IP65 rear: IP20 Operating System Windows Embedded CE 6.0 Prof. | Cardslot | | | CF + SD/MMC | | |
| Operating System Windows Embedded CE 6.0 Prof. | Housing | | | Die-cast aluminium | | |
| | Protection | | front: IP65 rear: IP20 | | | |
| Runtime Movicon 11 CE Standard | Operating System | | Wii | ndows Embedded CE 6.0 F | Prof. | |
| | Runtime | | Movicon 11 CE Standard | | | |



PanelPCs – Intelligent control and monitoring – with PC performance in the control cabinet.

With the PanelPC series you are best equipped for all control and monitoring tasks. Combinig the most modern performance features and the highly accurate and responsive projected capacitive touch-screen, our PanelPC series concetrates the highest usability in the smallest space.

The latest Intel Atom processor technology, large integrated work memory and display resolutions up to Full-HD in the 21.5" PanelPC leaves nothing to be desired. The Windows system environment which most users are familiar with, means there is no wasting time to learn how the system works. The PanelPCs also have many useful interfaces. The visual impression of your control cabinet is enhanced considerably by the high-quality materials of the PanelPCs.

The pre-installed operating system Windows Embedded Compact 7 or Windows Embedded Standard 7 comply with the latest status in the PC world and most of the users are familiar with it. In your visualization you can choose between your own programs or the latest pre-installed Movicon visualization.

Further features

- Latest Intel Atom processor technology
- High display resolution up to Full-HD at the 21,5" Panel
- Numerous interfaces for every application need
- Fanless construction

| | PPC 010 | PPC 015 | PPC 021 |
|---------------------|----------|---|-----------|
| Display size [Zoll] | 10,1 | 15,6 | 21,5 |
| Resolution [Pixel] | 1280x800 | 1366x768 | 1920x1080 |
| Touch screen | | PCAP | |
| Processor | | Intel Atom D2550 1860MHz | |
| Interfaces | | 2x RS232/422/485 (SUB-D) 4x USB-A 2x Ethernet 1x VGA 1x Audio out | |
| int. RFID Reader | | - | |
| Work Memory [MB] | | 2048 | |
| User Memory [MB] | | 2.048 - 16.384 | |
| Card slot | | CFast | |
| Casing | | aluminium | |
| Protection | | front: IP65 rear: IP20 | |
| Operating System | | WEC7 / WES7 (x32) | |
| Runtime | | - Movicon11 + Web-Visu - only Web-Visu | |



With more than 80,000 installed applications worldwide Movicon is one of the market leaders in the field of operating and monitoring. A platform for development for all Touch Panels whether large or small. Movicon is the key to easy use.

Movicon is the safe and reliable software solution for all those who develop and operate visualization applications and whose data also has to be available for mobile technologies. With the innovative and exclusive "XMLInside" technology the Movicon platform offers a unique development environment for HMI, SCADA, SoftLogic and data analysis.

The times for development become shorter, the solutions for the users become ergonomic, open, flexible, and easy to maintain. Movicon excels all other SCADA/HMI platforms with regard to openness, user friendliness, and performance. The unique Movicon software is completely XML based. Moreover, it relies on open and new upcoming technologies such as web service, SVG, OPC UA, SQL, ODBC, .NET and Java for Web-Client

solutions. Movicon is the standard for industrial automation, remote maintenance, supply industry and building automation. This universal platform is suitable for every field of application and completely hardware independent. It allows the development of operator stations of large scale systems with redundant client / server architecture. At the same time, it establishes applications and surfaces for WinCE supported mobile devices that communicate with PLC, networks, industrial or private field busses. The success of your project depends on how open and independent your applications are, and the amount of time and resources

development.



















Completely creatable graphic library

Easy, but effective instruction functions and graphic animations. 16 animation features for objects, among them motion, transparency functions, colors, color fillings, text editing etc.

Surface based on SVG graphics

Automatic adjustment of the graphics to display resolution with efficient rendering also for the bitmap image files.

Editable vector graphics

with powerful design and layout functions in 32 levels. The objects have an effective inheritance concept and support an Alias Parameter Management.

Process data storing in data loggers

with object-based management. Automatic ODBC connection for archives in relational data bases. In-memory data base support for the alternative recording in encodable text and XML files.

Automatic recipe control

on the basis of relational data bases or text files. Self-configurable recipes. Archiving in data bases and creation of the graphic user surface with only a few clicks.

Extremely efficient connectivity via the integrated I/O driver

Integrated specifications: OPC UA, DA and XML DA Client, as well as clientals also server-sides. Certificated OPC compatibility. Real-time data-separable, also via shared data base charts or via an I/O driver in the Shared Memory.

Data import from the PLC

All important drivers support the automatic tag import from the PLC program. Tag import from every system (e.g. MS Excel).

| Features | Movicon 11 CE | Movicon 11 WIN |
|---------------------------------|-------------------|---------------------------------------|
| available for | CE6/EC7 Panels | Panel PC with WES7 |
| I/O Bytes | 4096 | Default: 32 Option: 128, 512, 2048 |
| Screens | • | • |
| Graphics Library | • | • |
| Power templates | • | • |
| Alarms | max. 4096 | max. 2048 |
| Accelerators and Menus | • | • |
| Touch Screen | • | • |
| Event Historical Log | • | • |
| Dynamic language change | • | • |
| IL Logic (SoftLogik) | • | • |
| VBA Multi-threading | • | • |
| ActiveX- OCX | • | • |
| Debugger OnLine/Remote | • | • |
| Dynamics trends | • | • |
| Historical trends | • | • |
| Recipes | • | • |
| Data Logger | • | • |
| Reports | only Text Reports | Embedded Reports |
| Network operation | • | • |
| Multi-driver capable | max. 2 | max. 2 |
| SMS/E-Mail | • | • |
| OPC UA, DA und XML DA Client | • | • |
| VBA Drivers interface | • | - |
| Web Client | 2 Users | Option |
| | | |

• = unlimited / depends on the projekt

line displays



"Line displays have become very rare in the market. We still offer them. This is due to our policy of product sustainability, but also to the fact that our customers still ask for line displays. And we listen to our customers."



The text display TD 03

- Conceptualized for the deployment with our CPUs and Siemens CPUs
- Programmable with TD-Wizard



The operator panel OP 03

- For operating and monitoring small applications
- Programmable with OP-Manager or Siemens ProTool



The commander compact CC 03

- Controller and panel in one as there is a 100V PLC at the back that is also programmable with Siemens STEP7
- 16 digital inputs and outputs
- The panel is programmable with OP-Manager or Siemens ProTool

Its deployment is extremely space saving. And no matter which display you use the space in the control cabinet has always the same size. They are individually designable – with your logo, notes or whatever else.

VIPA Gesellschaft für Visualisierung und Prozessautomatisierung mbH

Drives Motion Controls Division Ohmstraße 4 91074 Herzogenaurach Germany Ph.: +49 (0) 9132 744-0 Fax: +49 (0) 9132 744-1864 e-mail: info@vipa.com www.vipa.com 11/2017 EK007809

